

# DETAILS OF CONCRETE BED & ENCASEMENT OF PIPE





TABLE										
INTERNAL ANG DIAMETER OF PIPE (mm) BEN		DESIGN PRESSURE (kg/m²)	SOIL COVER OVER PIPE Ds (mm)	H (m)	L1 (m)	L2 (m)	L3 (m)	(m)	B1 (m)	B2 (m)
100	90°	4.35	1000	0.70	0.75	0.40	0.35	0.77	0.70	0.35
100	45°	4.35	1000	0.60	0.55	0.30	0.25	0.57	0.60	0.30
100	22.5°	4.35	1000	0.45	0.45	0.25	0.20	0.46	0.50	0.25
100	90°	4.85	1000	0.70	0.80	0.45	0.35	0.82	0.70	0.35
100	45°	4.85	1000	0.60	0.55	0.30	0.25	0.57	0.60	0.30
100	22.5°	4.85	1000	0.50	0.45	0.25	0.20	0.47	0.50	0.25
100	90°	5.93	1000	0.80	0.75	0.40	0.35	0.78	0.80	0.40
100	45°	5.93	1000	0.65	0.65	0.35	0.30	0.67	0.70	0.35
100	22.5°	5.93	1000	0.50	0.55	0.30	0.25	0.56	0.50	0.25
150	90°	3.33	1000	0.85	0.85	0.45	0.40	0.88	0.90	0.45
150	45°	3.33	1000	0.70	0.70	0.40	0.30	0.72	0.70	0.35
150	22.5°	3.33	1000	0.55	0.55	0.30	0.25	0.57	0.50	0.25
250	90°	3.75	1000	1.25	1.25	0.70	0.55	1.29	1.30	0.65
250	45°	3.75	1000	1.00	1.05	0.60	0.45	1.08	1.00	0.50
250	22.5°	3.75	1000	0.80	0.80	0.45	0.35	0.82	0.80	0.40
250	90°	6.03	1000	1.45	1.45	0.80	0.65	1.49	1.50	0.75
250	45°	6.03	1000	1.15	1.25	0.70	0.55	1.28	1.10	0.55
250	22.5°	6.03	1000	0.95	0.90	0.50	0.40	0.93	0.90	0.45
350	90°	5.93	1000	1.80	1.80	1.00	0.80	1.86	1.80	0.90
350	45°	5.93	1000	1.45	1.55	0.85	0.70	1.59	1.50	0.75
350	22.5°	5.93	1000	1.20	1.15	0.65	0.50	1.19	1.20	0.60
500	90°	4.68	1000	2.15	2.05	1.15	0.90	2.12	2.20	1.10
500	45°	4.68	1000	1.70	1.80	1.00	0.80	1.85	1.70	0.85
500	22.5°	4.68	1000	1.40	1.35	0.75	0.60	1.39	1.40	0.70



## LEGEND:

— DIAMETER — BREADTH - LENGTH - HEIGHT — MILLIMETERS

### NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETRES AND LEVELS IN METRES UNLESS NOTED.
- 2. INVERT LEVEL OF PIPES SHALL BE AS PER RELEVANT NETWORK DRAWINGS.
- 3. NO CONCRETE SHALL BE PLACED AROUND JOINTS OF PIPELINE, UNTIL THAT LENGTH OF PIPE HAS PASSED SECTIONAL HYDRAULIC TEST.
- 4. STEEL FOR REINFORCEMENT SHALL BE HIGH YIELD STRENGTH DEFORMED BARS OF GRADE Fe 500
- 5. REINFORCEMENT LAP LENGTHS SHALL BE 50xDIAMETER OF SMALLER BAR.
- 6. CONCRETE TO BE USED SHALL BE OF GRADE M20 WITH 20mm DOWN GRADED AGGRAGATES CONFORMING TO SPECIFICATIONS.
- 7. CLEAR COVER TO REINFORCEMENT BOTTOM AND SIDES - 30mm
- 8. DURING CONSTRUCTION, IF GROUND WATER TABLE IS MET WITH, IT SHALL BE BROUGHT TO THE NOTICE OF ENGINEER FOR MAKING NECESSARY CHANGES IN THE DESIGN.
- 9. SOIL BENEATH AND BY THE SIDE OF THE THRUST BLOCK, WHICH ULTIMATELY BEARS THRUST THROUGH CONCRETE MEDIUM, MUST REMAIN UNDISTURBED. IN CASE ANY EXTRA EXCAVATION IS DONE IN TRENCHES, WHERE THE THRUST BLOCK IS TO BE PROVIDED, THE SAME SHALL BE FILLED WITH 1:4:8 CONCRETE
- 10. PIPES AND SPECIALS SHALL BE SUITABLY SUPPORTED WHILE CONCRETING THE THRUST BLOCK AS DIRECTED BY ENGINEER.
- 11. TESTING OF MAINS SHALL BE DONE AFTER CASTING OF THRUST BLOCKS AND COMPACTION OF BACKFILLING.
- 12. AT THE TIME OF TESTING, COMPACTED SOIL SHALL BE PLACED ON THE THRUST BLOCK UP TO THE ROAD LEVEL.
- 13. THRUST BLOCKS NEED TO BE PLACED AS PER SITE CONDITION

TYPICAL THRUST BLOCK

SIGN. INITIALS REVISIONS SIGN. P0 INITIALS SM MJ DVP NMS NMS REVISIONS CV EL IC ME CHD PE/PM APPD DRN DSN CLEARED

'P' (PRELIMINARY) ISSUES ARE NOT TO BE USED FOR CONSTRUCTION / FABRICATION BUT ARE ISSUED FOR LIMITED PURPOSES ONLY AS INDICATED IN THE SMALL BLOCK ABOVE THIS BLOCK.

CONSTRUCTION / FABRICATION WORK IS PERMITTED ON 15-04-2022 'R' (RELEASED) ISSUES ONLY.

INFORMATION CONTAINED WITHIN 'HOLD' IS NOT RELEASED FOR CONSTUCTION / FABRICATION. FIELD MUST GET DESIGN OFFICE TO CLEAR 'HOLDS' IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION/FABRICATION WORK RELATED TO 'HOLDS'.

SIGN. OF CLIENT:-ΑF FF SF

**PURPOSE: FOR TENDER ONLY** 

DO NOT SCALE

enquiry this set leads to the desired costs contents introductions only the "Clerk"; for the Project under consideration, which provided for the sole purpose of permitting the recipient to evaluate the internation submitted hermatic. In consideration, receipt of this document; usess agreed to in contrary in the Centruct, the recipient operates to minist make internation confidence and to an expression confidence decises the information configuration to ministen the confidence accept that there is no obligation to maintain the confidentiality of any information which was income to the recipient prior to recipied upon the information in the information FILE NAME 12503A-CV-30582-Rev-P0

DETAILED DESIGN CONSULTANCY, HP-SHIVA (PACKAGE CS09)

IRRIGATION, HORTICULTURE, ORCHARDS AND VALUE CHAIN DEVELOPMENT

TYPICAL DETAILS OF THRUST BLOCK




## TATA CONSULTING ENGINEERS LIMITED


**MUMBAI** 


SCALE : NTS TCE.12503A-CV-3082-WS-30582 DC & DISC: DEL-CV

PO

ISSUE







LIMITED PURPOSES ONLY AS INDICATED IN THE SMALL BLOCK ABOVE THIS BLOCK.

CONSTRUCTION / FABRICATION WORK IS PERMITTED ON

INFORMATION CONTAINED WITHIN 'HOLD' IS NOT RELEASED FOR CONSTUCTION / FABRICATION. FIELD MUST GET DESIGN OFFICE TO CLEAR 'HOLDS' IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION, FABRICATION WORK RELATED TO 'HOLDS'.

'R' (RELEASED) ISSUES ONLY.

NMS

NMS

APPD

### **LEGEND**

REINFORCED CEMENT CONCRETE PLAIN CEMENT CONCRETE

CAST IRON CEMENT MORTAR

THICK

- POLY VINYL CHLORIDE

- INTERNAL CLEAR DIAMETER OF PIPELINE

— DUCTILE IRON

DOUBLE SOCKET FLANGE

CENTER LINE

---- MAKEUP PIECE

#### **NOTES**

- 1. ALL DIMENSIONS ARE IN MM. & LEVELS ARE IN METRES.
- 2. GRADE OF REINFORCEMENT CEMENT CONCRETE SHALL 1:2:4
- THE ACTUAL GLS AND ILS OF ALL CHAMBERS SHALL BE FIXED BY THE CONTRACTOR IN CONSULTATION WITH THE ENGINEER-IN-CHARGE.
- 4. EXACT ORIENTATION AND LOCATION OF THE CHAMBERS SHALL BE DECIDED BY THE CONTRACTOR IN CONSULTATION WITH THE ENGINEER-IN-CHARGE.
- 5. CEMENT SHALL BE ORDINARY PORTLAND TYPE CONFORMING TO IS: 269 UN,
- MAXIMUM SIZE OF AGGREGATES SHALL BE 20mm DOWNGRADED FOR RAFT, WALLS, BEAMS AND SLABS.
- 7. BACKFILLING AROUND WALLS TO BE DONE UNIFORMLY ALL ROUND IN SUCCESSIVE LIFTS OF EQUAL HEIGHT AS PER SPECIFICATION BACKFILLING SHALL BE DONE ONLY WHEN WHEN DIRECTED BY ENGINEER.
- 8. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH TENDER SPECIFICATION.
- CHAMBER TO BE PLASTERED INTERNALLY WITH CEMENT MORTAR 1:3 IN 12MM THICKNESS.
- GRADE OF CONCRETE SHALL BE M20 WITH MAXIMUM 20mm DOWN GRADED AGGREGATES CONFORMING TO SPECIFICATION.
- 11. FOR LOCATION OF VALVE CHAMBERS REFER NETWORK DISTRIBUTION DRAWING. THE CONTRACTOR SHALL OBTAIN ENGINEER'S APPROVAL FOR ALL VALVE CHAMBER LOCATIONS AND LEVELS BEFORE EXECUTION.
- THE ARRANGEMENT RELATED TO VALVE AND FITTINGS SHOWN IN THE DRAWING ARE INDICATIVE ONLY. BEFORE CONSTRUCTION, ARRANGEMENT OF VALVE & FITTINGS SHALL BE PROVIDED BY THE CONTRACTOR TO ENGINEER FOR APPROVAL.

DETAILED DESIGN CONSULTANCY, HP-SHIVA (PACKAGE CS09)

IRRIGATION, HORTICULTURE, ORCHARDS AND VALUE CHAIN DEVELOPMENT

TYPICAL DETAILS OF SCOUR VALVE AND AIR VALVE CHAMBER



: NTS

DC & DISC: DEL-CV

SCALE

DO NOT SCALE

FILE NAME 12503A-CV-30585-Rev-P0

TATA CONSULTING ENGINEERS LIMITED

MUMBAI

TCE.12503A-CV-3082-WS-30585

P0

ISSUE

SM MJ DVP

DSN

CHD

CV EL IC ME

CLEARED


REVISIONS


REVISIONS

SIGN.

P0 INITIALS

Ø OF PIPE





SECTION 1-1

MK

MK

DK

DK

PE/PM APPD

'P' (PRELIMINARY) ISSUES ARE NOT TO BE USED FOR CONSTRUCTION / FABRICATION BUT ARE ISSUED FOR LIMITED PURPOSES ONLY AS INDICATED IN THE SMALL BLOCK ABOVE THIS BLOCK.

15-04-2022 'R' (RELEASED) ISSUES ONLY.

CONSTRUCTION / FABRICATION WORK IS PERMITTED ON

INFORMATION CONTAINED WITHIN 'HOLD' IS NOT RELEASED FOR CONSTUCTION / FABRICATION. FIELD MUST GET DESIGN OFFICE TO CLEAR 'HOLDS' IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION/FABRICATION WORK RELATED TO 'HOLDS'.

#### LEGEND

ATTDT. — — ATTENDANT

RCC --- REINFORCED CEMENT CONCRETE

TYP --- TYPICAL

GL --- GROUND LEVEL

### NOTES

- 1. ALL DIMENSIONS ARE IN MILLIMETRES AND LEVELS IN METRES UNLESS NOTED.
- 2. DO NOT SCALE THE DRAWING. FOLLOW FIGURED DIMENSIONS ONLY.
- 3. GRADE OF CONCRETE SHALL BE M20 WITH MAXIMUM 20mm DOWNGRADED AGGREGATES CONFORMING TO IS 456.
- 4. SAFE BEARING CAPACITY OF SOIL IS TAKEN AS 10T/Sq.m. AT FOUNDING LEVEL AND SAME IS TO BE CONFIRMED AT SITE BEFORE EXECUTION.
- 5. PLAIN CEMENT CONCRETE UNDER FOUNDATION SHALL BE OF GRADE M10 CONFORMING TO IS 456.
- 6. IF ANY LOOSE SOIL IS ENCOUNTERED AT FOUNDING LEVEL DURING CONSTRUCTION, IT SHOULD BE BROUGHT TO THE NOTICE OF THE ENGINEER.
- 7. IF GROUND WATER TABLE IS ENCOUNTERED DURING CONSTRUCTION, IT SHOULD BE BROUGHT TO THE NOTICE OF THE ENGINEER FOR MAKING APPROPRIATE CHANGES IN THE DESIGN.
- 8. THE SPACING OF CONSTRUCTION JOINT SHALL NOT BE MORE THAN 1.20M.

DETAILED DESIGN CONSULTANCY, HP-SHIVA (PACKAGE CS09)

IRRIGATION, HORTICULTURE, ORCHARDS AND VALUE CHAIN DEVELOPMENT

ΑE EΕ SE TYPICAL DETAILS OF PUMP HOUSE

: NTS

DC & DISC: DEL-CV

TATA

SCALE

**PURPOSE: FOR TENDER ONLY** 

y Notice and Version Control This document contains confidential information for use only by "" for the Project under consideration, which is provided for the sole purpose of permitting the recipient information saminflet hermith. It consideration of recipient of the document, unless upped to in control, the recipient agrees to motivation such information in confidence and to not reproduce or otherwise discloses from a vary person admitted there is no distillation to their interest and control yellow of the control of th

DO NOT SCALE

FILE NAME 12503A-CV-30586-Rev-P1

TATA CONSULTING ENGINEERS LIMITED

**MUMBAI** 

. TCE.12503A-CV-3082-GA-30586

FILE NAME: F-093-Rev-R1.DWG

DRN

SM AD DVB

SM LD/AD DVB

DSN

CHD

CV | EL | IC | ME

CLEARED

P1 INITIALS


REVISIONS


REVISIONS

SIGN.

PO INITIALS

SSUE





### **LEGEND:**

DIA--- DIAMETER H---- STAGE HEIGHT

THK---- THICKNESS

FGL----FINISHED GROUND LEVEL

RB---- ROOF BEAM

#### NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETRES AND LEVELS IN METRES UNLESS NOTED.
- 2. DO NOT SCALE THE DRAWING. FOLLOW FIGURED DIMENSIONS ONLY.
- 3. GRADE OF CONCRETE SHALL BE M30 WITH MAXIMUM 20mm DOWNGRADED AGGREGATES CONFORMING TO IS 456.
- 4. STEEL FOR REINFORCEMENT SHALL BE HIGH YIELD STRENGTH DEFORMED BARS OF GRADE FE-500 CONFORMING TO IS:1786.
- 5. SAFE BEARING CAPACITY OF SOIL IS TAKEN AS 10T/Sq.m. AT FOUNDING LEVEL AND SAME IS TO BE CONFIRMED AT SITE BEFORE EXECUTION.
- 6. PLAIN CEMENT CONCRETE UNDER FOUNDATION SHALL BE OF GRADE M10 CONFORMING TO IS 456.
- 7. IF ANY LOOSE SOIL IS ENCOUNTERED AT FOUNDING LEVEL DURING CONSTRUCTION, IT SHOULD BE BROUGHT TO THE NOTICE OF THE ENGINEER.
- 8. IF GROUND WATER TABLE IS ENCOUNTERED DURING CONSTRUCTION, IT SHOULD BE BROUGHT TO THE NOTICE OF THE ENGINEER FOR MAKING APPROPRIATE CHANGES IN THE
- 9. THE SPACING OF CONSTRUCTION JOINT SHALL NOT BE MORE THAN 1.20M.

SECTION ELEVATION

DETAILED DESIGN CONSULTANCY, HP-SHIVA (PACKAGE CS09) IRRIGATION, HORTICULTURE, ORCHARDS AND VALUE CHAIN DEVELOPMENT

GENERAL ARRANGEMENT OF INTAKE WELL

P1 INITIALS SM LD/AD DVP REVISIONS AS PER CLIENT OBSERVATION SIGN. P0 INITIALS SM LD/AD DVP NMS NMS REVISIONS CV EL IC ME DRN DSN CHD PE/PM APPD

NMS NMS 27-05-2022 'P' (PRELIMINARY) ISSUES ARE NOT TO BE USED FOR CONSTRUCTION / FABRICATION BUT ARE ISSUED FOR LIMITED PURPOSES ONLY AS INDICATED IN THE SMALL BLOCK ABOVE THIS BLOCK.

CONSTRUCTION / FABRICATION WORK IS PERMITTED ON 15-04-2022 'R' (RELEASED) ISSUES ONLY.

INFORMATION CONTAINED WITHIN 'HOLD' IS NOT RELEASED FOR CONSTUCTION / FABRICATION.
FIELD MUST GET DESIGN OFFICE TO CLEAR 'HOLDS' IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION/FABRICATION WORK RELATED TO 'HOLDS'.

PURPOSE: FOR TENDER ONLY DO NOT SCALE SCALE FILE NAME 12503A-CV-30587-Rev-P1 DC & DISC: DEL-CV

ΕE

SE

SIGN. OF CLIENT:-

ΑE




: NTS


TATA CONSULTING ENGINEERS LIMITED


**MUMBAI** 


TCE.12503A-CV-3082-GA-30587

TCE FORM NO. 093 R1









# NO\_FINE CONCRETE MANHOLE COVER RCC COLUMN IN CC (1:2:4) GL C 0.15m THK-RCC SLAB IN CC 1///// 1:2:4 -ŚPRING LVL MANHOLE (MEDIUM DUTY) -6.00m-RCC BEAM (0.3X0.6)-6.00m SECTIONAL PLAN NO FINE CONCRETE L.W.L. (1:6)200 1 DRAW DOWN LVL

### LEGEND:

CC----CEMENT CONCRETE
RCC----REINFORCED CEMENT CONCRETE
LVL-----LEVEL
GL-----GROUND LEVEL

### NOTES:

- 1. ALL DIMENSIONS AND ELEVATIONS ARE IN METRES UNLESS OTHERWISE NOTED.
- 2. ALL DIMENSIONS INDICATED ARE CLEAR INSIDE DIMENSIONS.

DETAILED DESIGN CONSULTANCY, HP-SHIVA (PACKAGE CS09)
IRRIGATION, HORTICULTURE, ORCHARDS AND VALUE CHAIN DEVELOPMENT

SIGN. OF CLIENT:
JE AE EE SE

PURPOSE: FOR TENDER ONLY

TYPICAL DETAILS OF PERCOLATION WELL

-L-IRON 75X75X10mm -L-IRON 65X65X6mm

SECTION ELEVATION

'P' (PRELIMINARY) ISSUES ARE NOT TO BE USED FOR CONSTRUCTION / FABRICATION BUT ARE ISSUED FOR LIMITED PURPOSES ONLY AS INDICATED IN THE SMALL BLOCK ABOVE THIS BLOCK.

CONSTRUCTION / FABRICATION WORK IS PERMITTED ON

CONSTRUCTION / FABRICATION WORK IS PERMITTED ON 'R' (RELEASED) ISSUES ONLY.

INFORMATION CONTAINED WITHIN 'HOLD' IS NOT RELEASED FOR CONSTRUCTION / FABRICATION.

IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION / FABRICATION WORK RELATED TO 'HOLDS'.

FIELD MUST GET DESIGN OFFICE TO CLEAR 'HOLDS'.

IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION / FABRICATION WORK RELATED TO 'HOLDS'.

placy Motice and Version Control This document contains confidential information for use only by the "Client."; for reject under consideration, which is provided for the sole purpose of permitting the recipient to evaluate the various submitted benefits. In consideration of recipi of this document unless argued to in contray in the Contract; ecipient agrees to maintain such information is confidence and to not reproduce or otherwise disclose this information such submitted in confidence and to not reproduce or otherwise disclose this information most action mich was brown to the recipient prior to receipt in any information from Tato Consulting Explanes Limited, or in received without comes publicly forms through no fourth of recipient, or Index Consulting Explanes Limited, or in received without four of confidentiality to the Consulting Explanes Limited, and the Consulting Explanes Limited and Consulting Explanes Limited Annual Consulting Explanes Limited and Consulting Explanes Limited and Consulting Explanes

TATA

: NTS

DC & DISC: DEL-CV

TATA CONSULTING ENGINEERS LIMITED


MUMBAI


. TCE.12503A-CV-3082-GA-30592


2 ISSUE


FILE NAME: F-093-Rev-R1.DWG

TCE FORM NO. 093 R1









### GENERAL NOTES:

- 1. THIS SLD SHOWS THE SCHEME FOR DISTRIBUTION OF THE POWER WITHIN THE PROJECT BATTERY LIMIT & SHALL be READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRGS. RATINGS, SIZES & QUANTITIES OF EQUIPMENTS MARKED AS '\*' NEED TO BE CALCULATED / PROVIDED BASED ON SYSTEM REQUIREMENT AS TENDER SPECIFICATIONS. CONTRACTOR SHALL SUBMIT THE EQUIPMENT SIZING CALCULATIONS & CORRESPONDING SWITCH GEAR RATING ALONG WITH THE BID.
- 2. THE CONTRACTOR HAS TO DO DETAIL ENGINEERING OF HV & LV SYSTEM AND WORK OUT THE RATING OF EACH COMPONENT AS PER DESIGN CRITERIA GIVEN IN TENDER & EQUIPMENT SIZING CALCULATIONS AS APPROVED BY ENGINEER-IN -CHARGE.
- HV SYSTEM:
- a) INTER TRIPPING & CLOSING INTERLOCK SHALL BE PROVIDED BETWEEN TRANSFORMER FEEDER (11KV) AND LT PANEL INCOMER (0.415KV) SIDE.
- b) CT /PT UNIT FOR HT METERING AND TVM SHALL BE AS PER DISCOM.
- 4. <u>LV SYSTEM:</u>
- a) <u>ACB</u>
- 415V SWITCHBOARD INCOMER/ BUS COUPLER ACB SHALL BE FP, EDO TYPE WITH MICROPROCESSOR-BASED O/C, S/C & INBUILT E/F AND UV RELEASES.
- ALL OUTGOING ACBS SHALL BE TP, EDO TYPE WITH MICROPROCESSOR-BASED O/C, S/C & INBUILT E/F RELEASES EXCEPT FOR APFC WHICH SHALL BE MDO TYPE WITH THERMAL MAGNETIC RELEASES.
- IN ALL LT SWITCHBOARDS, CURRENT RATING ABOVE 630A SHALL HAVE ACBs.
- -ALL ACBS SHALL BE WITH ICS=ICU=ICW=100%.
- b) MCCE
- 415V SWITCHBOARD INCOMER/ BUSCOUPLER MCCB (>=250A) SHALL BE FP FIXED TYPE WITH MICROPROCESSOR BASED O/C, S/C & E/F RELEASES AND OUTGOING MCCB (>=250A) SHALL BE TP FIXED TYPE WITH MICROPROCESSOR BASED O/C, S/C & E/F RELEASES EXCEPT FOR APFC AND WHICH SHALL HAVE TM BASED O/C, S/C & E/F RELEASES WITH EXTERNAL E/F MODULE. ALL INCOMER/ OUTGOING MCCB (<250A) SHALL HAVE TM BASED O/C, S/C & E/F RELEASES WITH EXTERNAL E/F MODULE.
- ALL MCCB SHALL BE WITH Ics=Icu=100%.
- 5. ALL INDICATIONS, SHUNT TRIP/CLOSING COILS OF HT/ LT BREAKERS (VCBS/ ACBS) WILL BE ON 30/110V DC CONTROL SUPPLY. SPRING CHARGING MOTORS OF ALL BREAKERS WILL BE ON 230V AC SUPPLY. IF, DC SUPPLY IS NOT AVAILABLE FROM EXTERNAL SOURCE, IT SHALL BE DERIVED FROM INBUILT DC POWER PACK SUITABLE FOR ACCEPTING 230V AC SUPPLY FROM EXTERNAL SOURCE.
- 6. IN MCC, ALL MOTOR STARTER COMPONENTS RATING SHALL BE SELECTED AS PER MANUFACTURER'S TYPE-2 CO-ORDINATION CHART. MOTOR STARTERS SHALL BE COMPLETE WITH SINGLE PHASING PREVENTER. AMMETERS IN MOTOR FEEDERS SHALL BE PROVIDED WITH SUPPRESSED SCALE UP TO 6 TIMES FULL LOAD CURRENT FOR INDICATING STARTING CURRENT. ALL MOTOR FEEDERS UP TO 0R EQUAL TO 5.5 KW SHALL HAVE DIRECT CONNECTED AMMETERS IN Y PHASE & MOTORS GREATER THAN 5.5KW WILL BE PROVIDED WITH ONE CT & AMMETER.
- 7. THE ON, OFF AND TRIP POSITION OF MCCB/ MPCB SHALL BE CLEARLY INDICATED. ROTARY OPERATING HANDLE FOR MCCBs/ MPCBs WITH THE DOOR CLOSED INTERLOCK SHALL BE PROVIDED. ALL MCCB/ MPCB FEEDERS ON ALL PANELS SHALL BE PROVIDED WITH ON/OFF/TRIP INDICATING LAMPS THROUGH AUXILIARY CONTACTS. WHEREVER STARTER FEEDER PROVIDED WITH MPCB BUT WITHOUT OVERLOAD RELAY, MPCB SHALL HAVE INBUILT OVERLOAD PROTECTION FEATURE.
- 8. 110 OR 220V AC CONTROL SUPPLY FOR LT PCC/ MCC SHALL BE DERIVED FROM CONTROL TRANSFORMER(S) OF ADEQUATE RATING. INTERLOCKING BETWEEN TWO CONTROL SUPPLIES SHALL BE PROVIDED SUCH THAT ENERGIZED SECTION CATERS FOR THE NEED OF THE PCC/ MCC PANEL.
- 9. MCCB & MPCB TERMINALS SHALL BE SHROUDED AND SHALL BE DESIGNED TO RECEIVE CABLE LUGS FOR RELEVANT CABLE SIZES.
- 10. ALL INDICATING LAMPS SHALL BE MULTICHIP LED TYPE.
- 11. MULTIFUNCTION METER FOR MEASURING ALL POWER & ENERGY PARAMETERS SHALL HAVE AN ACCURACY CLASS OF 1.0 OR BETTER, WITH RS 485 COMM PORT.
- 12. ALL CONTACTORS / TIMERS SHALL BE DIN RAIL MOUNTED.
- 13. UNDER STEADY STATE CONDITIONS, VOLTAGE DROP IN VARIOUS SECTIONS OF ELECTRICAL SYSTEM SHALL BE LIMITED TO A) CABLES BETWEEN TRANSFORMER SECONDARY TO PMCC 2 % AND B) CABLES BETWEEN PMCC TO MOTOR- 3%. UNDER MOTOR STARTING CONDITIONS, THE CORRESPONDING VOLTAGE DROP SHALL NOT AFFECT THE OPERATION OF THE MOTOR CONTROLS OR THE ABILITY OF THE MOTOR TO START AND RUN EFFECTIVELY AND IN ANY EVENT SHALL NOT EXCEED 15%. FAULT CLEARING TIME TO BE CONSIDERED WHILE SIZING OF CABLES SHALL BE AS A) PCC INCOMER 1 SEC AND B) TRANSFORMER PRIMARY: 0.16 SEC.
- 14. UNLESS SPECIFIED, ALL SWITCHBOARDS SHALL BE FREE STANDING, COMPARTMENTALIZED, EXTENSIBLE ON BOTH SIDES WITH HEIGHT NOT EXCEEDING 2300MM. ENCLOSURE PROTECTION OF SWITCHBOARDS SHALL BE AS PER TENDER.
- 15. WHEREVER APPLICABLE, SEPARATE PANEL FOR HVAC, FIRE AND PLUMPING PUMP WILL BE PART OF RESPECTIVE BOQ.
- 16. WHEREVER APPLICABLE, PROVISION OF ONE-WAY NET METERING SHALL BE PROPOSED IN THE SLD FOR INTEGRATION OF THE SOLAR WITH THE DISTRIBUTION SYSTEM.
  THIS METHODOLOGY NEEDS TO BE VERIFIED WITH THE STATE ELECTRICITY BOARD AND THE SOLAR VENDORS. SOLAR POWER SUPPLY WILL NOT BE ON WHEN DG IS
  ON.
- 17. WHEN TWO DG'S ARE OPERATING IN PARALLEL THEN PROVISION OF NEUTRAL CONTRACTOR INTERLOCKING SHOULD BE SUCH THAT ONLY ONE DG WILL BE EARTHED.
- 18. MCB USED FOR STANDARD NETWORK SHALL HAVE 'C' CHARACTERISTIC CURVE.
- 19. EACH TYPE & RATING OF OUTGOING FEEDER SHALL HAVE 10% SPARE OR MINIMUM ONE NUMBER.

														SIGN. OF	CLIENT:-		
														JE	AE	EE	SE
	SIGN.												'P' (PRELIMINARY) ISSUES ARE NOT TO BE USED FOR CONSTRUCTION / FABRICATION BUT ARE ISSUED FOR	PURP	OSE : FOR	R TENDER	RONLY
H	INITIALS												LIMITED PURPOSES ONLY AS INDICATED IN THE SMALL		DO NOT	SCALE	
I	REVISIONS												BLOCK ABOVE THIS BLOCK.	Descriptory Maline and Vennine	Carles This damment analysis	antidadid information for use a	nly by the Client : for the
	SIGN.											<u> </u>	CONSTRUCTION / FABRICATION WORK IS PERMITTED ON 'R' (RELEASED) ISSUES ONLY.	Project under consideration, at submitted herewith, in conside	hich is provided for the sale pur ration of receipt of this documen mation in confidence and to not	pose of permitting the recipient t it: unless coreed to in contrary i	o evaluate the information
) [	INITIALS	KKS	ASB	ASB						MK	DK	18-04-2022	INFORMATION CONTAINED WITHIN 'HOLD' IS NOT	outside the recipient's organis	ation; except that there is no abi	ligation to maintain the confident	ally of any information which
	REVISIONS												RELEASED FOR CONSTUCTION / FABRICATION. FIELD MUST GET DESIGN OFFICE TO CLEAR 'HOLDS'	known through no fault of re- from a third party pains no o	cipient, or Tala Consulting Enginee obligation of confidentiality to Tale	ers Limited, or is received without a Consulting Engineers Limited, A	obligation of confidentiality
ΙĒ		DRN	DSN	CHD	CV	EL	IC	ME		PE/PM	ADDD	DATE	IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION/	version over rides all and any	kind of offers, assumptions, del in writing or otherwise given under	iverables and contracts submitted	verbally (and subsequently
ᄩ	ואוטן	אוכטו				CLE	ARED			APPD	(dd=mm-yyyy)	1	FILE NAME	: 12503A-	-EL-40004	-Rev-P0	

LEGEND:							
- <del></del>	LIGHTNING ARRESTER	R	RELAYING				
<u> </u>	ISOLATER WITH EARTH SWITCH	l	INSTRUMENTATION				
<i>▶</i>	ISOLATER WITH D.O.	25	SYNCHRONIZING RELAY				
	FUSE	27/59	UNDER/OVER VOLTAGE RELAY				
	CIPCUIT RREAKER(ACR (ACR)	81	UNDERFREQUENCY RELAY				
<u> </u>	CIRCUIT BREAKER(ACB/VCB) DRAW-OUT TYPE	(50)	INST. O/C PROTECTION				
	CIRCUIT BREAKER(ACB/VCB)	(50N)	INST. E/F PROTECTION				
<u> </u>	NON DRAW-OUT TYPE'	(51)	IDMT. O/C PROTECTION				
<b>&gt;</b>	мссв	95	TRIP SUPERVISION RELAY				
<b>þ</b> ∿	MPCB	49W	WINDING TEMP. HIGH INDICATOR WITH ALARM & TRIP CONTACTS				
, to	мсв	490	OIL TEMP. HIGH INDICATOR WITH ALARM & TRIP CONTACTS				
<b>‡</b>	CABLE GLAND	63 X	PRESSURE RELIEF DEVICE				
$\otimes$	INDICATING LAMP	(63) T	BUCHHOLZ RELAY				
•	PUSH BUTTON	OSR	OIL SURGE RELAY				
€,3	CURRENT TRANSFORMER (CT)	MOG	MAGNETIC OIL GAUGE				
	(FIGURE INDICATES NO. OF CT's)	86	LOCK OUT RELAY				
)K	DOTENTIAL TRANSFORMER	SC	SPRING CHARGED				
	POTENTIAL TRANSFORMER	TCH	TRIP CIRCUIT HEALTHY				
(A)	TRANSFORMER	SP	SERVICE POSITION				
<u>₩</u>	THE WAST STRIKE TO	TP	TEST POSITION				
TVM	TRI VECTOR METER		ELECTRICAL CABINET				
an .	CHOKE	(MFM)	MULTIFUNOTION ASTER				
AS	AMMETER SELECTOR SWITCH	MIFINI	MULTIFUNCTION METER				
A	ANALOG AMMETER	NET_	NET ENERGY				
(VS)	VOLTMETER SELECTOR SWITCH	METER V	NET ENERGY METER				
V	ANALOG VOLTMETER	TNC	TOID MELITAM OLOGE				
Ø-0	PUSH BUTTON STATION	(i)	TRIP—NEUTRAL—CLOSE SWITCH (KEY OPERATED)				
E.M.I.	ELECTRICAL - MECHANICAL INTERLOCK	ETPB	EMERGENCY TRIP PUSH BUTTON				
O O O	TWO MOMENTARY CONTACT PB WITH THREE INDICATING LAMPS	‡	CONTACTOR				
	(R = RED, G = GREEN, A = AMBER)	NC	NORMALLY CLOSED				
L−R □	LOCAL REMOTE SELECTOR SWITCH	NO	NORMALLY OPEN				

DETAILED DESIGN CONSULTANCY, HP-SHIVA (PACKAGE CS09)
IRRIGATION, HORTICULTURE, ORCHARDS AND VALUE CHAIN DEVELOPMENT

TYPICAL SLD FOR LIS PUMPING STATION WITH LT/HT METERING GENERAL NOTES & LEGENDS



# TATA CONSULTING ENGINEERS LIMITED

MUMBAI

white our rises at end only laid at other, assumptions, delinerates and contracts sateritistal winday (and subsequently communicated in writing or otherwise discussed in writin

P0

ISSUE

PΩ

SSUE